



Art.No.: 4900260

# CREOS

## CREOS

### LIGHT SOURCE

Type	RGBL LED
Count	18
TLCI	77
TM-30-15 Rf/Rg	104 / 80

### OPTICAL SYSTEM

Output	up to 7,600 lm
Peak Luminous Intensity	673 kcd
Min. Zoom	4.3°
Max. Zoom	52°
Zoom Ratio	1:12

### DYNAMIC EFFECTS

CTC	2,500 – 10,000 K
Color Mixing	RGB   RGBL   x,y

### MOVEMENT

Tilt	190°, 16 bit   motorized
------	--------------------------

### CONTROL & PROGRAMMING

DMX Channels	20   33   39   48   84   63   81
Control Modes	7
Protocols	DMX (USITT DMX512-A)   RDM (ANSI/ESTA E1.20)   Art-Net   GLP iQ.Mesh   LumenRadio CRMX

### CONNECTIONS

Power connection	REAN powerCON True1 In/Out
Signal connection	REAN XLR 5-Pin In/Out REAN etherCon In/Out (failsafe)

### ELECTRICAL SPECIFICATIONS

Power input	100 – 240 V AC / 50 – 60 Hz
Max. Power	800 W

### THERMAL SPECIFICATIONS

Max. ambient temperature	40 °C / 104 °F
Min. ambient temperature	-10 °C / 14 °F

### INSTALLATION

Location	Outdoor temporary   Indoor permanently
----------	--

### CONSTRUCTION

Protection Rating	IP 65
-------------------	-------

### DIMENSIONS & WEIGHT

Height	375 mm / 14.76 in
Width	388 mm / 15.27 in
Depth	218 mm / 8.58 in
Weight netto	20.3 kg / 44.75 lbs