



PDP-1, Art.Nr.: 6501
PDP-1/S, Art.Nr.: 6502S



PDP-2, Art.Nr.: 6506
PDP-2/S, Art.Nr.: 6507S



PDP-3 /DF163-16
Art.Nr.: 6526



PDS 16 S
Art.Nr.: 6518



PDS 32 S
Art.Nr.: 6528

Power Distribution

	PDP-1 /S	PDP-2 /S	PDP-3 /DF163-16
Input Plug	CEE 400 V/16 A with 2m cable	CEE 400 V/32 A with 2m cable	CEE 400 V/63 A with 2m cable
Mains Voltage	380–400 V AC, 50 Hz	380–400 V AC, 50 Hz	380–400 V AC, 50 Hz
Fuse Standard	6 x C16A	3 x C16A	2 x RCCB 40A Type A plus 12 x RCBO C16A
/S Version	6 x RCBO C16A	3 x RCBO C16A	12 x RCBO C16A
Outputs Front	1 x SCHUKO 230 V/16 A 1x CEE 400 V/32 A	3 x SCHUKO® 230 V/16 A 1x CEE 400 V/16 A	none
Outputs Back	6 x SCHUKO® 230 V/16 A	6 x SCHUKO® 230 V/16 A	6 x SCHUKO® 230 V/16 A
Dimensions	482 x 193.5 x 88 mm / 19 x 76.2 x 3.5 in	482 x 193.5 x 88 mm / 19 x 76.2 x 3.5 in	482 x 313 x 132 mm / 19 x 12.3 x 5.2 in
Weight	5 kg / 11 lbs	4 kg / 9 lbs	11.5 kg / 25 lbs

PDS 16 S**PDS 32 S**

IP Rating	IP 44	IP 44
Input Plug	MENNEKES® CEE 400 V/16 A	MENNEKES® CEE 400 V/32 A
Mains Voltage	380–400 V AC, 50 Hz	380–400 V AC, 50 Hz
Fuse	3 x RCBO C16A	3 x RCBO C16A
Output	6 x SCHUKO® 230 V/16 A	6 x SCHUKO® 230 V/16 A
Phase indicator lights	yes	yes
Dimensions	510 x 410 x 200 mm / 20.1 x 16.1 x 7.9 in	855 x 855 x 350 mm / 33.7 x 33.7 x 13.8 in
Weight	7 kg / 15 lbs	7.5 kg / 16.5 lbs