

LED-Luminaire LUCIDUS 600 OUT



TYPE

Profile-mounted / workplace luminaire
 Material Aluminium
 Color Silver matt
 Item Number N2014-A02OUT

ADVANTAGES

Robust construction, maintenance-free, flicker-free light without UV and IR content, daylight white, compatible with almost all commonly available profiles, flexible application, easy cleaning. Protection Rating equals IP 67.

LIGHT DATA

Rated Power	34 W
Power Consumption	37 W
Input Voltage	DC 24 V
Luminous Flux	4,600 lm
Luminous Efficacy	135.5 lm/W
Color Temperature	~6,000 K
Color Designation	Daylight white
Color Rendering Index	83 Ra (CRI)
Beam Angle	120 Degrees
Connection	open wires, 5 m
LED Lifetime	> 50,000 h
LED Type	LED-Modul SMD
LED Number	240
Dimmable	Yes, with dimmable power supply

TENDER TEXT

Product Profile Light / Workplace Light; Material Aluminium; Color Silvermatt; Rated Power in Watt 34; Power Consumption in Watt 37; Input Voltage in Volt DC 24; Luminous Flux in Lumen 4,600; Luminous Efficacy in Lumen/Watt 135.5; Color Temperature in Kelvin 6,000; Color Designation Daylight white; Color Rendering Index Ra (CRI) 83; TLCl (Qa) 73; Beam Angle in Degrees 120; Connection DC Socket 5.5mm; LED Lifetime in Hours >50,000; LED Type LED-Modul SMD (fixed); LED Number 240; Dimmable with LED sensordimmer; Protection Rating equals IP 67; Operating Temperature -10°C to +50°C; Total Length in mm 646; Illuminated Length in mm 630; Total Width in mm 45; Illuminated Width in mm 40; Total Height in mm 45; Channel for fasteners (Rear) in mm 8; Gross Weight in kg 2.35; Ned Weight in kg 2.00; Energy Efficiency Class A++; Energy Efficiency Index 0.12; Weighted Energy Consumption in kWh/1,000h 37


FEATURES



MOUNTING

8mm channel for fasteners on rear

LIGHT DISTRIBUTION



ADDITIONAL DATA

Protection Rating	equals IP 67
Operating Temperature	-10°C to +50°C
Gross Weight	2.35 kg
Ned Weight	2.00 kg
Energy Efficiency Class	A++
Energy Efficiency Index	0.12
Weighted Energy Consumption	37 kWh/1,000h

DIMENSION

Total Length	646 mm
Illuminated Length	630 mm
Total Width	45 mm
Illuminated Width	40 mm
Total Height	45 mm