

MAD MAXX



Preliminary Data

Key Facts

- massive homogeneously illuminated 750 mm diameter beam
- no external focus points within the outgoing beam
- fully illuminated fat light aperture same as beam size

FROM THIN LINES OF LIGHT TO FAT BEAMS

The unique GLP MAD MAXX is the first real LED FAT BEAM light with a massive 750mm beam diameter. This makes it the only beam fixture that is on a similar level with the proven 3kW and 7kW xenon beam lights. The GLP MAD MAXX is designed to use as a SkyBeam to the Air or as a super Fat Beam Effect on Stages or Events and has no visible external focus points within the outgoing beam. Very impressive is the fully illuminated fat light aperture with the same diameter as the beam itself – that's makes the fixture look giant if placed in the stage.

A virtual Iris let you reduce the beam diameter. For great and intensive color variety the CW (ColorWheel) Version gives access to a 16bit color wheel with fade able CTO down to 2500K and 18 fix colors. In addition to a simple basic mode, the fixtures also offers a segment or multibeam control mode for individual control of the 3 segments or 19 beams. A pattern mode let you quickly add a selection of 2-color static or 1-color dynamic pattern effects if you are in a hurry.

Technical Data (1/2)*

LIGHT SOURCE

Type	White Light LED
Power	90 W
Count	19
Lifetime	20,000 h
LED Refresh Rate	adjustable up to 25 kHz
CCT	6,500 K
CRI	Default: 70+ with High CRI: 90

OPTICAL SYSTEM

Output	up to 68,000 lm
Beam angle	1.6°
Peak luminous intensity	4.7 Mcd
Output aperture diameter	750 mm / 295.3 in
Output Lenses	19 lenses with full circular aperature, diameter 750 mm / 295.3 in

DYNAMIC EFFECTS

Color Mixing	mechanical color wheel
Dimmer	0 – 100 %, electronic

Technical Data (2/2)*

MOVEMENT

Pan	540° normal, 650° extended, 16 bit
Tilt	200°, 16 bit

CONTROL & PROGRAMMING

DMX Channels	tbd
Control Modes	Basic Pattern Segments MultiBeam
Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20) Art-Net sACN GLP iQ.Mesh LumenRadio CRMX
High-Res Channels	Dimmer Pan Tilt Color Wheel
Dimming Curves	Linear Soft S-Curve
Performance Modes	Fast Normal (Balanced) Smooth
Fan Modes	Regulated
Setting and addressing	backlit graphic LCD 4 Button Menu Navigation DMX RDM GLP iQ.Mesh
Firmware Update	DMX Link via DProg iQ.Tool GLP iQ.Mesh

CONNECTIONS

Power connection	Neutrik powerCON True1 In
Signal connection	Neutrik XLR 5-Pin In/Out Neutrik etherCON In/Out (failsafe)

ELECTRICAL SPECIFICATIONS

Power input	180 – 240 V AC / 50 – 60 Hz
Power supply unit	Auto-ranging electronic switch mode
Max. Power	2,500 W

THERMAL SPECIFICATIONS

Cooling Type	combined convection and forced air
Temperature range, Operating	-10 °C – 45 °C / 14 °F – 115 °F
Thermal Protection	automatic
Total heat dissipation	8,500 BTU/hr

INSTALLATION

Mounting	Safety Cable attachment point Mounting/Rigging Baseplate
Orientation	ground standing vertical hanging
Location	Indoor permanent, outdoor temporary

CONSTRUCTION

Housing color	Black
Material	High-impact flame-resistant thermoplastic Aluminum Steel
Protection Rating	IP 65
Construction Features	Base with sufficiently stable standing surface Tilt Lock Base Handles 4 crane eye-lets at Yoke Mechanic Sun Protection Rigging Plate GLP FX.Port

SHIPPING

Tourpack	1-way Flightcase Rigging Bracket
----------	--------------------------------------

DIMENSIONS & WEIGHT

Height	1,248 mm / 49.1 in
Width	1,043 mm / 41.1 in
Depth	789 mm / 31.1 in
Weight netto	195 kg / 430 lbs

ARTICLE NUMBERS

MAD MAXX CW	7992
-------------	------

* Preliminary Data.
Subject to change.