

IMPRESSION

X5 IP



Preliminary Data

Technical Data (1/2)*

LIGHT SOURCE

Type	RGLB LED
Power	36 W
Count	19
Lifetime	50,000 h
LED Refresh Rate	Low: 550 Hz Optimal: dynamic PWM Algorithm High 1: 4,600 Hz High 2: 13,000 Hz

Values rounded. For detailed information, contact GLP Support

CCT	6,500 K
Duv	perfect white point matches with low Duv values
CRI	8,000 K: 87 6,500 K: 86.7 3,200 K: 84.8
TLCI	8,000 K: 90 6,500 K: 88.5 3,200 K: 74.1
TM-30-15 Rf/Rg	6.500 K: 87 / 105 3.200 K: 85 / 110

OPTICAL SYSTEM

Output	up to 11,400 lm
Max. Peak Luminous Intensity	1.8 Mcd

Min. Zoom	3.6°
Max. Zoom	63°
Zoom Ratio	1:17
Output Lenses	19 lenses with full circular aperture, diameter 278 mm / 10.9 in

DYNAMIC EFFECTS

Color mixing	RGB RGLB x,y
CTC	2,500 – 10,000 K
CQC	High Output (HO) High Quality (HQ) Desaturation
Color wheel	virtual, 64 LEE referenced colors
Magenta/Green-Shift	yes
Tungsten Simulation	8x linked to fix CCT 8x relative to Colormix
Pattern Effects	50 dynamic pattern macros with special effects
Zoom	3.6° – 63°
Dimmer	0 – 100 %, 16 bit
Shutter	variable speed, with effects

MOVEMENT

Pan	540° normal, 16 bit
Tilt	16 bit

Technical Data (2/2)*

CONTROL & PROGRAMMING

DMX Channels	M1: CH24 M2: CH35 M3: CH41 M4: CH89 M5: CH70 M6: CH89
Control Modes	M1: Basic M2: Normal M3: Segment M4: Multipix Advanced M5: Multipix Com- pressed RGB M6: Multipix Compressed RGLB
Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20) Art-Net sACN GLP iQ.Mesh LumenRadio CRMX
High-Res Channels	Pan Tilt Intensity Colormix
Dimming Curves	Linear Soft S-Curve
Performance Modes	Fast Normal (Balanced) Smooth
Fan Modes	Regulated High Medium Low Off
Subfixture Mode	Normal Independent
White Points	8,000 K 5,600 K 4,200 K 3,200 K
PWM	Low Optimal High 1 High 2
Setting and addressing	backlit graphic LCD 4 Button Menu Navigation DMX RDM iQ.Service App
Others	1 Scene Stand Alone Art-Net/ sACN Node Data Con- version GLP iQ.Mesh NFC FPO Port (Flexible Protocol Option)
Firmware Update	DMX Link via DProg GLP iQ.Mesh

CONNECTIONS

Power connection	Neutrik powerCON True1 In/Out
Signal connection	Neutrik XLR 5-Pin In/Out Neutrik etherCON port A & B (failsafe) GLP FX.Port

ELECTRICAL SPECIFICATIONS

Power input	100 – 240 V AC / 50 – 60 Hz
Power supply unit	Auto-ranging electronic switch mode
Max. Power	750 W

THERMAL SPECIFICATIONS

Cooling Type	combined convection and forced air
Temperature range, Operating	-10 °C – 45 °C / 14 °F – 115 °F
Thermal Protection	automatic

INSTALLATION

Mounting	2 pair of 1/4-turn locks Safety Cable attachment point 2x M10 Screw Thread for direct mount of Rigging Clamp
Orientation	Any
Location	Indoor permanent, outdoor temporary

CONSTRUCTION

Housing color	Black
Material	High-impact flame-resistant thermoplastic Aluminum Steel
Protection Rating	IP 65
Construction Features	prepared for external accessories Tilt-Lock-System

SHIPPING

Single fixture	Cardboard
Tourpack	2-way

DIMENSIONS & WEIGHT

Height	
Head home	487 mm / 19.1 in
Head vertical	530 mm / 20.8 in
Width across yoke	377 mm / 14.8 in
Depth	324 mm / 12.7 in
Weight netto	21 kg / 46 lbs

ARTICLE NUMBERS

impression X5 IP	7793
------------------	------

* Preliminary Data.
Subject to change.

01/2025