



Preliminary Data

Technical Data (1/2)*

LIGHT SOURCE

Type	White Light LED
Strobe Line	White Light LED
RGBW Panels	RGBW LED
Power	700 W

DYNAMIC EFFECTS

Dimmer	16 bit
--------	--------

MOVEMENT

Tilt	190°, 16 bit
------	--------------

CONTROL & PROGRAMMING

DMX Channels	19 37 227 245
Control Modes	4
Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20)
High-Res Kanäle	Dimmer Tilt
Dimming Curves	Linear Soft
Performance Modes	Fast Normal Smooth
Fan Modes	Regulated High Medium Low

Setting and addressing

Control panel with backlit graphic display | 4 Button Menu Navigation | DMX | RDM

Others

Stand Alone Scene | Pattern FX Engine | Multi-patch for media servers | FVP Protocol

Firmware Update

DMX Link via DProg | iQ.Mesh

CONNECTIONS

Power connection

Neutrik powerCON TRUE1 In/Out

Signal connection

Neutrik XLR 5-Pin In/Out | etherCON In/Out (failsafe)

ELECTRICAL SPECIFICATIONS

Power input

100 – 240 V AC / 50 – 60 Hz

Power supply unit

Auto-ranging electronic switch-mode

THERMAL SPECIFICATIONS

Cooling Type

combined convection and forced air

Temperature range

5 °C / 40 °F to 45 °C / 115 °F

Technical Data (2/2)*

INSTALLATION

Mounting	2 eyelets for safety cable Safety cable attachment point 2 pairs of 1/4-turn locks
Orientation	Any
Protection Rating	IP 65
Location	Indoor permanently, outdoor temporary

CONSTRUCTION

Housing Color	Black
Housing Material	High-impact flameresistant thermo-plastic Aluminum Steel Metal Plates
Protection Rating	IP 65
Construction Features	Changeable frontscreen

DIMENSIONS & WEIGHT

Height	313 mm / 10 in
Width across yoke	412 mm / 16.2 in
Depth head vertical	172 mm / 6.7 in
Weight netto	14 kg / 30.8 lbs

* Preliminary Data.
Subject to change.

12/2024