KNV LINE

DESCRIPTION

The KNV system from GLP brings a whole new dynamic to entertainment lighting, groundbreaking in both design and functionality. KNV Line and KNV Dot work as independent units or combine seamlessly together. In combination they provide a whole new level of versatility and freedom in design, all in an outdoor rated housing, allowing them to be used on a multitude of events and occasions.

A truly multi-functional fixture, the KNV system is equally happy being used as a pixel mapped surface, strobe, blinder, washlight, or scenic element.

Art. No.: 7780L

KEY FEATURES

LIGHT SOURCE
LED Power Pixel: 1 x White Light + 16 x RGB

MODULAR SYSTEM
for individual, creative designs

PIXEL PITCH
continuous alignment between fixtures

DETAILS

Further information, pictures, and technical data as well as downloads for KNV Line at our website: www.glp.de

Direct-Link:

IP54 | DMX | RDM | sACN | Art NET | DIM | 115 – 230 VOLT | 1.8 kg | 170 WATT | RGBW

KNV LINE

KNV Line – Installation overview

TECHNICAL DATA

LIGHT SOURCE

Power Pixel	1 x 30 W White
	16 x 0.25 W RGB
Power Pixel Count	5

CONTROL

Control Modes	8
Setting and addressing	back-lit Graphic Display, 4 Button Menu Navigation, DMX, RDM
Protocol	USITT DMX-512 ArtNET
Cooling type	temperature controlled, overheating protection

CONNECTORS (PSU)

Signal	Neutrik PowerCon True1 In/Out, 5x Power-Data Cable ODS 6 PIN tail out
Power	Neutrik powerCON TRUE1 In/Out

DIMENSIONS & WEIGHT

Length	50 mm / 1.97 in
Width	250 mm / 9.9 in
Height	165 mm / 6.5 in
Weight	2 kg / 4.4 lbs

AVAILABLE ACCESSORIES

PRODUCT	DESCRIPTION	ART. NO.
KNV PSU Rigging	IP 54 / PSU for up to 5x KNV Line	7780P
KNV Installation Bracket Line	fix Bracket for mounting of KNV Line	778023