

Exo Wash 30

FUSION
by GLP



Key Facts

- 7 x 40 W OSRAM LED RGBW
- Zoom 4° – 54°
- Pixel LED Control
- IP65
- True1 & XLR-5 In/Out

IP65 MOVING HEAD WASH FROM FUSION BY GLP

- Zoom range from 4° to 54° for beam and wash application
- Fast Pan & Tilt Movements
- Original OSRAM LEDs for best colours
- Pixel Control for visual effects
- Front Head Mounting with magnetic holders and M3 insert threads for barndoor/filters/Anti-Glare
- Anti-Fog System with additional pressure vent system
- W-DMX optional
- Battery-buffered OLED Display for easy setup without power
- IP65 classification for true outdoor use
- True1 & XLR-5 connections
- RDM compliant
- Tough Die-Casting Housing



08/2025

Technical Data

LIGHT SOURCE

Type	RGBW LED
Power	40 W
Count	7
Lifetime	20,000 h

OPTICAL SYSTEM

Min. Zoom	4°
Max. Zoom	54°

DYNAMIC EFFECTS

Color mixing	RGBW, independently variable 0 – 100 %
CTC	2.500 – 10.000 K, variable
Zoom	motorized
Dimmer / Shutter	0 – 100 % continuous electronic regular and random strobe and pulse effects

MOVEMENT

Pan	540°
Tilt	267°
Position correction system	Position feedback

CONTROL & PROGRAMMING

DMX Channels	13 22 38 50
Control Modes	4
Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20) LumenRadio CRMX (optional)
Dimming curves	Linear Soft
Fan Modes	Regulated High Medium Low
Setting and addressing	OLED display with 4 buttons self-charging buffer battery
Firmware Update	Update Unit via DMX Line

CONNECTIONS

Power connection	Neutrik powerCON True1 In/Out
Signal connection	Neutrik XLR 5-Pin In/Out

ELECTRICAL SPECIFICATIONS

Power input	100 – 240 V AC / 50 – 60 Hz
Power supply unit	auto-ranging electronic switch-mode
Max. Power	230 W

THERMAL SPECIFICATIONS

Cooling type	combined convection and forced air
Max. ambient temperature	45 °C / 113 °F
Min. ambient temperature	-10 °C / 14 °F

INSTALLATION

Mounting	1 pair of 1/4-turn locks safety cable attachment point rubber feet
Orientation	Any
Location	Outdoor

CONSTRUCTION

Housing color	Black
Housing material	Aluminum
Protection Rating	IP 65
Construction Features	Pan/Tilt-Lock-System integrated base handles

SHIPPING

Tourpack	2-way
----------	-------

DIMENSIONS & WEIGHT

Height	
Head vertical	521 mm / 20.5 in
Width across yoke	380 mm / 14.96 in
Depth	
Head vertical	279 mm / 11 in
Weight netto	19.7 kg / 43.43 lbs

ARTICLE NUMBERS

Exo Wash 30	4900230
-------------	---------