

HIGH BAY LIGHT H2



TYPE

Product Pendant Light / High Bay Light
 Material Aluminium
 Color Silver matt
 Item Number 3777

ADVANTAGES

Type H1 High Bay Lights by GLP provide highly effective lighting for workplaces, high bays and large hall areas up to 8 meters high. Their compact design, toughened safety glass, robust construction and simple installation make them suitable for a wide range of applications.


LIGHT DATA

Power Consumption	99 W
Input Voltage	AC 100 – 240 V
Luminous Flux	13,222 lm
Luminous Efficacy	133 lm/W
Color Temperature	4,100 K
Color Designation	neutral white
Color Rendering Index	86 Ra (CRI)
Beam Angle	110 Degrees
Connection	Connection box, incl. cable entry
LED Lifetime	> 50,000 h
LED Type	LED-Modul SMD
LED Number	216
Dimmable	Yes, with PWM, 1 – 10 V, Poti 10 – 100 kΩ + Dali

FEATURES



LIGHT DISTRIBUTION



MOUNTING

Attachment rings on housing for suspension

ADDITIONAL DATA

Protection Rating	IP 50
Operating Temperature	-10°C to +50°C
Gross Weight	6.9 kg
Ned Weight	6.1 kg
Energy Efficiency Class	A++
Energy Efficiency Index	0.1
Weighted Energy Consumption	99 kWh/1,000 h

DIMENSION

Total Length	267 mm
Illuminated Length	248 mm
Total Width	330 mm
Illuminated Width	295 mm
Total Height	85 mm