

-GLP-



Art.No.: 7678

JD  **II** **IP**

JDC2 IP

LIGHT SOURCE

Type	White Strobe LED RGB LED
CRI	tbc

OPTICAL SYSTEM

Total Output	
Beam	47,000 lm
Plate	20,000 lm
Beam and Plate	70,000 lm
Dimension Output	2x 377 x 111 mm /
Lens	2x 14.8 x 4.4 in

MOVEMENT

Tilt	184°, 16 bit
------	--------------

CONTROL & PROGRAMMING

Control Modes	M1: Simple Strobe (CH12 / 42 Fixture) M2: Simple Strobe Pro (CH27 / 18 Fixture) M3: Segment 2 (CH51 / 10 Fixture) M4: Segment 12 (CH92 / 5 Fixture) M5: Segment 24 (CH128 / 4 Fixture; DEFAULT)
Protocols	DMX (USITT DMX512-A) RDM (ANSI/ESTA E1.20) LumenRadio CRMX (optional) iQ.Mesh

ELECTRICAL SPECIFICATIONS

Max. Power	1,500 W
------------	---------

CONSTRUCTION

Protection Rating	IP 65
-------------------	-------

DIMENSIONS & WEIGHT

Height head straight up	354 mm / 13.94 in
Height head vertical	452 mm / 17.8 in
Width across yoke	444 mm / 17.48 in
Depth head vertical	230 mm / 17.48 in
Weight netto	23.5 kg / 51.8 lbs

