

# LED-Luminaire LUCIDUS Mini 50



## TYPE

Profile / Display luminaire  
Material Aluminium  
Color Silver matt  
Item Number N2014-M5

## ADVANTAGES

Robust construction, maintenance-free, flicker-free light without UV and IR content, flexible application, neutral white, easy cleaning, Protection Rating equals IP 67.

## LIGHT DATA

Rated Power	13.5 W
Power Consumption	13.7 W
Input Voltage	DC 24 V
Luminous Flux	730 lm
Luminous Efficacy	54.4 lm/W
Color Temperature	4,900 K
Color Designation	neutral white
Color Rendering Index	86 Ra (CRI)
Beam Angle	110 Degrees
Connection	M8 Socket, 3-pin
LED Lifetime	> 50,000 h
LED Type	LED-Modul SMD
LED Number	40
Dimmable	Yes, with dimmable power supply

## MOUNTING

8mm channel for fasteners on rear

## ADDITIONAL DATA

Protection Rating	equals IP 67
Operating Temperature	-10°C to +50°C
Gross Weight	435 g
Ned Weight	300 g
Energy Efficiency Class	A
Energy Efficiency Index	0.27
Weighted Energy Consumption	13.7 kWh/1,000h


## TENDER TEXT

Product Profile / Display luminaire; Material Aluminium; Color Silver matt; Rated Power in Watt 13.5; Power Consumption in Watt 13.7; Input Voltage in Volt DC 24; Luminous Flux in Lumen 730; Luminous Efficacy in Lumen/Watt 54.4; Color Temperature in Kelvin 4,900; Color Designation neutral white; Color Rendering Index Ra (CRI) 86; TLCI (Qa) 74; Beam Angle in Degrees 110; Connection DC Socket 3-pin; LED Lifetime in Hours > 50,000; LED Type LED-Modul SMD (fixed); LED Number 40; Dimmable with LED dimmable power supply; Protection Rating equals IP 67; Operating Temperature -10°C to +50°C; Total Length in mm 530; Total Width in mm 23; Total Height in mm 23; Channel for fasteners (Rear) in mm 8; Gross Weight in g 435; Ned Weight in g 300; Energy Efficiency Class; Energy Efficiency Index 0.27; Weighted Energy Consumption in kWh/1,000h 13.7

## FEATURES



## LIGHT DISTRIBUTION



## DIMENSION

Total Length	530 mm
Total Width	23 mm
Total Height	23 mm