


LED-Luminaire LUCIDUS Mini 10



TYPE

Profile / Display luminaire
Material Aluminium
Color Silver matt
Item Number N2014-M1

ADVANTAGES

Robust construction, maintenance-free, flicker-free light without UV and IR content, flexible application, neutral white, easy cleaning, Protection Rating equals IP 67.

LIGHT DATA

Rated Power	2.7 W
Power Consumption	2.9 W
Input Voltage	DC 24 V
Luminous Flux	145 lm
Luminous Efficacy	49 lm/W
Color Temperature	4,900 K
Color Designation	neutral white
Color Rendering Index	86 Ra (CRI)
Beam Angle	110 Degrees
Connection	M8 Socket, 3-pin
LED Lifetime	> 50,000 h
LED Type	LED-Modul SMD
LED Number	8
Dimmable	Yes, with dimmable power supply

MOUNTING

8mm channel for fasteners on rear

ADDITIONAL DATA

Protection Rating	equals IP 67
Operating Temperature	-10°C to +50°C
Gross Weight	165 g
Ned Weight	90 g
Energy Efficiency Class	A
Energy Efficiency Index	0.20
Weighted Energy Consumption	2.9 kWh/1,000h


TENDER TEXT

Product Profile / Display luminaire; Material Aluminium; Color Silver matt; Rated Power in Watt 2.7; Power Consumption in Watt 2.9; Input Voltage in Volt DC 24; Luminous Flux in Lumen 145; Luminous Efficacy in Lumen/Watt 49; Color Temperature in Kelvin 4,900; Color Designation neutral white; Color Rendering Index Ra (CRI) 86; TLCI (Qa) 74; Beam Angle in Degrees 110; Connection DC Socket 3-pin; LED Lifetime in Hours > 50,000; LED Type LED-Modul SMD (fixed); LED Number 8; Dimmable with dimmable power supply; Protection Rating equals IP 67; Operating Temperature -10°C to +50°C; Total Length in mm 130; Total Width in mm 23; Total Height in mm 23; Channel for fasteners (Rear) in mm 8; Gross Weight in g 165; Ned Weight in g 90; Energy Efficiency Class; Energy Efficiency Index 0.20; Weighted Energy Consumption in kWh/1,000h 2.9

FEATURES



LIGHT DISTRIBUTION



DIMENSION

Total Length	130 mm
Total Width	23 mm
Total Height	23 mm