


LED-Luminaire LUCIDUS Mini 40



TYPE

Profile / Display luminaire
Material Aluminium
Color Silver matt
Item Number N2014-M4

ADVANTAGES

Robust construction, maintenance-free, flicker-free light without UV and IR content, flexible application, neutral white, easy cleaning, Protection Rating equals IP 67.

LIGHT DATA

Rated Power	10.8 W
Power Consumption	11 W
Input Voltage	DC 24 V
Luminous Flux	545 lm
Luminous Efficacy	50.4 lm/W
Color Temperature	4,900 K
Color Designation	neutral white
Color Rendering Index	86 Ra (CRI)
Beam Angle	110 Degrees
Connection	M8 Socket, 3-pin
LED Lifetime	> 50,000 h
LED Type	LED-Modul SMD
LED Number	32
Dimmable	Yes, with dimmable power supply

MOUNTING

8mm channel for fasteners on rear

ADDITIONAL DATA

Protection Rating	equals IP 67
Operating Temperature	-10°C to +50°C
Gross Weight	365 g
Ned Weight	250 g
Energy Efficiency Class	A
Energy Efficiency Index	0.26
Weighted Energy Consumption	11 kWh/1,000h


TENDER TEXT

Product Profile / Display luminaire; Material Aluminium; Color Silver matt; Rated Power in Watt 10.8; Power Consumption in Watt 11; Input Voltage in Volt DC 24; Luminous Flux in Lumen 545; Luminous Efficacy in Lumen/Watt 50.4; Color Temperature in Kelvin 4,900; Color Designation neutral white; Color Rendering Index Ra (CRI) 86; TLCl (Qa) 74; Beam Angle in Degrees 110; Connection DC Socket 3-pin; LED Lifetime in Hours > 50,000; LED Type LED-Modul SMD (fixed); LED Number 32; Dimmable with LED dimmable power supply; Protection Rating equals IP 67; Operating Temperature -10°C to +50°C; Total Length in mm 430; Total Width in mm 23; Total Height in mm 23; Channel for fasteners (Rear) in mm 8; Gross Weight in g 365; Ned Weight in g 250; Energy Efficiency Class; Energy Efficiency Index 0.27; Weighted Energy Consumption in kWh/1,000h 11

FEATURES



LIGHT DISTRIBUTION



DIMENSION

Total Length	430 mm
Total Width	23 mm
Total Height	23 mm