



KNV Dot
Art.No.: 7780D



KNV Line
Art.No.: 7780L

KNV SYSTEM

KNV DOT & LINE

LIGHT SOURCE

Power Pixel 1 x 30 W White
16 x 0.25 W RGB

Power Pixel count Dot: 1; Line: 5

CONTROL

Control Modes 8

Setting and Addressing Control panel with backlit graphic display
4 Button Navigation, DMX, RDM

Protocol USITT DMX-512 ArtNET

Cooling temperature controlled, overheating protection

CONNECTORS (PSU)

Signal connection Neutrik PowerCon True1 In/Out, 5x Power-Data Cable ODS 6 PIN tail out

Power Input DMX 5pin In/Out, etherCon In/Out (fail safe), 5x Power-Data Cable ODS 6 PIN tail out

OPERATING CONDITIONS

Mains voltage 100–240 VAC / 50–60Hz

Power PSU (Watt @ 230V) 800 W

Max. ambient temperature 40 °C / 113 °F

Operating Position any

Protection Rating IP54

EEC A

EEL 0.218

Ec (kWh/1.000h) 742

INSTALLATION

Mounting KNV Connector
KNV Yoke

HOUSING COLORS

Standard color black

DIMENSIONS & WEIGHT

KNV DOT

Length 92 mm / 3.62 in

Width 92 mm / 3.62 in

Height 76 mm / 3.0 in

Weight 0.7 kg / 1.54 lbs

KNV LINE

Length 59 mm / 1.93 in

Width 250 mm / 9.8 in

Height 161.5 mm / 6.36 in

Weight 2.17 kg / 4.78 lbs